

Appl. No. 09/814,260
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

In the Claims

Claims 1-67 are canceled.

68. [Previously Presented] A semiconductor workpiece processing method comprising:

providing a semiconductor processor system having a process chamber adapted to process a semiconductor workpiece;

processing the semiconductor workpiece within the process chamber using a process fluid;

monitoring the process fluid;

controlling at least one operation of the semiconductor processor system responsive to the monitoring; and

wherein the monitoring comprises monitoring turbidity of the process fluid.

69. [Original] The method according to claim 68 further comprising providing a sample of the process fluid and the monitoring comprises monitoring the sample.

70. [Original] The method according to claim 69 further comprising providing the sample of the process fluid in a substantially static state and the monitoring comprises monitoring the process fluid in the substantially static state.

Appl. No. 09/814,260
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

71. [Original] The method according to claim 69 wherein the monitoring comprises comparing the sample of the process fluid with a signature.

72. [Original] The method according to claim 68 further comprising flushing a connection configured to transport the process fluid and the controlling comprises controlling the flushing.

73. Canceled.

74. [Original] The method according to claim 68 further comprising supplying the process fluid to the process chamber and the monitoring is during the supplying.

75. [Original] The method according to claim 68 further comprising draining the process fluid from the process chamber and the monitoring is during the draining.

76. [Original] The method according to claim 68 wherein the processing comprises processing using a pad, and further comprising extracting process fluid from the pad during the processing and the monitoring comprises monitoring the process fluid after the extracting.

Appl. No. 09/814,280
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

77. [Original] The method according to claim 68 further comprising transporting the process fluid relative to the process chamber using a connection and the monitoring comprises monitoring accumulation of particulate matter within the connection.

78. [Original] The method according to claim 68 further comprising:
receiving a start-up command of the semiconductor processor system; and
priming a connection configured to transport the process fluid using a flush fluid responsive to the receiving.

79. [Original] The method according to claim 78 wherein the priming comprises priming with flush fluid comprising the process fluid.

80. [Previously Presented] The method according to claim 78 wherein the monitoring comprises monitoring the turbidity of the flush fluid during the priming and the controlling comprises controlling the priming.

81. [Original] The method according to claim 68 further comprising:
receiving a halt command of the semiconductor processor system; and
flushing a connection configured to transport the process fluid responsive to the receiving.

Appl. No. 09/814,260
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

82. [Original] The method according to claim 81 wherein the flushing comprises flushing with flush fluid comprising a rinse fluid.

83. [Previously Presented] The method according to claim 81 wherein the monitoring comprises monitoring the turbidity of the flush fluid during the flushing and the controlling comprises controlling the flushing.

84. [Original] The method according to claim 68 further comprising mixing plural components to provide the process fluid and the controlling comprises controlling the mixing.

85. [Original] The method according to claim 68 further comprising storing historical data of the process fluid after the monitoring.

86. [Original] The method according to claim 68 wherein the processing comprises chemical-mechanical polishing the semiconductor workpiece.

87. [Currently Amended] A semiconductor workpiece processing method comprising:

providing a semiconductor processor system adapted to process a semiconductor workpiece using a process fluid;

Appl. No. 09/814,280
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

~~providing a sample of the process fluid;~~
providing the a sample of the process fluid in a substantially static state;
monitoring the sample of the process fluid; and
controlling an operation of the semiconductor processor system responsive to the
monitoring.

88. [Original] The method according to claim 87 wherein the monitoring comprises monitoring the turbidity of the sample of the process fluid.

89. [Original] The method according to claim 87 wherein the monitoring comprises monitoring differential turbidity of the sample of the process fluid.

90. [Original] The method according to claim 89 wherein the monitoring comprises monitoring differential turbidity with respect to different moments in time.

91. [Original] The method according to claim 87 wherein the monitoring comprises comparing the sample of the process fluid with a signature.

92. [Currently Amended] The method according to claim 87 wherein the controlling the operation comprises controlling a flush system to at least one of prime and rinse a connection configured to transport the process fluid.

Appl. No. 09/814,260
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

93. [Original] The method according to claim 87 wherein the controlling comprises controlling a recirculation system to recirculate the process fluid.

94. [Original] The method according to claim 87 further comprising monitoring an operation of the semiconductor processor system and the providing the sample comprises providing the sample during defined operations of the semiconductor processor system.

95. [Original] The method according to claim 87 further comprising storing historical data of the process fluid after the monitoring.

Claims 96-102 are canceled.

103. [Currently Amended] A semiconductor workpiece processing method comprising:

providing a semiconductor processor ~~system~~ adapted to process a semiconductor workpiece using a process fluid;

transporting the process fluid relative to the semiconductor processor ~~system~~;

monitoring turbidity of the process fluid; and

recirculating the process fluid after the monitoring.

Appl. No. 09/814,260
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

104. Cancel.

105. [Currently Amended] The method according to claim 103 further comprising wherein the transporting comprises supplying the process fluid to a process chamber of the semiconductor processor system a semiconductor processor after the recirculating.

106. [Original] The method according to claim 103 further comprising controlling the recirculating responsive to the monitoring.

Claims 107-117 are canceled.

118. [Currently Amended] A semiconductor workpiece processing method comprising:

providing a semiconductor processor system adapted to process a semiconductor workpiece using a process fluid;

transporting the process fluid relative to the semiconductor processor system using a connection;

monitoring accumulation of particulate matter within the connection; and

controlling at least one operation of the a semiconductor processor system comprising the semiconductor processor responsive to the monitoring.

Appl. No. 09/814,260
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

119. [Original] The method according to claim 118 wherein the transporting comprises transporting using a substantially horizontal connection.

120. [Original] The method according to claim 119 wherein the monitoring comprises monitoring in a substantially vertical direction.

121. [Original] The method according to claim 118 wherein the monitoring comprises monitoring turbidity.

122. [Original] The method according to claim 118 wherein the controlling comprises controlling a flushing operation of the connection responsive to the monitoring.

123. [Original] The method according to claim 118 wherein the controlling comprises controlling a recirculating operation of the connection responsive to the monitoring.

124. [Original] The method according to claim 118 wherein the transporting comprises supplying process fluid to a process chamber of the semiconductor processor system.

Appl. No. 09/814,260
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

125. [Original] The method according to claim 118 wherein the transporting comprises draining process fluid from a process chamber of the semiconductor processor system.

126. [Currently Amended] A method of delivering transporting a semiconductor workpiece process fluid relative to a semiconductor processor comprising:

providing a semiconductor workpiece process fluid;

transporting the semiconductor workpiece process fluid relative to a semiconductor processor; and

monitoring turbidity of the semiconductor workpiece process fluid.

127. Cancel.

128. [Original] The method according to claim 126 wherein the monitoring comprises comparing the semiconductor workpiece process fluid with a signature.

129. [Original] The method according to claim 126 wherein the providing comprises mixing a plurality of components of the semiconductor workpiece process fluid, and further comprising controlling the mixing responsive to the monitoring.

Appl. No. 09/814,260
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

130. [Previously Presented] A semiconductor workpiece processing method comprising:

providing a semiconductor processor system having a process chamber adapted to process a semiconductor workpiece;

processing the semiconductor workpiece within the process chamber using a process fluid;

monitoring the process fluid;

controlling at least one operation of the semiconductor processor system responsive to the monitoring; and

flushing a connection configured to transport the process fluid, and the controlling comprises controlling the flushing.

131. [Previously Presented] A semiconductor workpiece processing method comprising:

providing a semiconductor processor system having a process chamber adapted to process a semiconductor workpiece;

processing the semiconductor workpiece within the process chamber using a process fluid;

monitoring the process fluid;

controlling at least one operation of the semiconductor processor system responsive to the monitoring; and

Appl. No. 09/814,260
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

transporting the process fluid relative to the process chamber using a connection and the monitoring comprises monitoring accumulation of particulate matter within the connection

132. [Previously Presented] A semiconductor workpiece processing method comprising:

providing a semiconductor processor system having a process chamber adapted to process a semiconductor workpiece;

processing the semiconductor workpiece within the process chamber using a process fluid;

monitoring the process fluid;

controlling at least one operation of the semiconductor processor system responsive to the monitoring;

receiving a start-up command of the semiconductor processor system; and

priming a connection configured to transport the process fluid using a flush fluid responsive to the receiving.

133. [Previously Presented] The method according to 132 wherein the priming comprises priming with flush fluid comprising the process fluid.

Appl. No. 09/814,260
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

134. [Previously Presented] The method according to 132 wherein the monitoring comprises monitoring turbidity of the flush fluid during the priming and the controlling comprises controlling the priming.

135. [Previously Presented] A semiconductor workpiece processing method comprising:

providing a semiconductor processor system having a process chamber adapted to process a semiconductor workpiece;

processing the semiconductor workpiece within the process chamber using a process fluid;

monitoring the process fluid;

controlling at least one operation of the semiconductor processor system responsive to the monitoring;

receiving a halt command of the semiconductor processor system; and

flushing a connection configured to transport the process fluid responsive to the receiving.

136. [Previously Presented] The method according to 135 wherein the flushing comprises flushing with flush fluid comprising a rinse fluid.

Appl. No. 09/814,260
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

137. [Previously Presented] The method according to 135 wherein the monitoring comprises monitoring turbidity of the flush fluid during the flushing and the controlling comprises controlling the flushing.

138. [Previously Presented] The method according to claim 87 wherein the providing the sample comprises controlling extraction of the sample of the process fluid from a distributor configured to provide the process fluid.

139. [New] The method according to claim 68 wherein the monitoring comprises monitoring the sample of the process fluid in the substantially static state.

140. [New] The method according to claim 68 wherein the monitoring comprises monitoring a percent of solids present within a liquid of the process fluid.

141. [New] The method according to claim 103 wherein the monitoring comprises monitoring the process fluid being transported.

142. [New] The method according to claim 103 wherein the monitoring comprises monitoring a percent of solids present within a liquid of the process fluid.

Appl. No. 09/814,260
Amdt. Dated 7/7/2005
Office Action mailed 4/7/2005

143. [New] The method according to claim 103 wherein the recirculating comprises recirculating responsive to the monitoring.

144. [New] The method according to claim 103 wherein the recirculating comprises recirculating responsive to the turbidity of the process fluid being out of specification.

145. [New] The method according to claim 126 wherein the monitoring comprises monitoring during the transporting.

146. [New] The method according to claim 126 wherein the monitoring comprises monitoring a percent of solids present within a liquid of the process fluid.

147. [New] The method according to claim 126 wherein the transporting comprises delivering the semiconductor workpiece process fluid to the semiconductor processor.